

B811 SERIES LIGHTED BOLLARD

OPTIONAL LIGHTED TOPS

L1 **L2** **L3** **L6**

DIFFUSER TYPE	
CPC Clear Polycarbonate	<input type="checkbox"/>
WGL White Glass	<input type="checkbox"/>
WPC White Polycarbonate	<input type="checkbox"/>

VOLTAGE	
QT (Quad Tap 120, 208, 240, 277)	<input type="checkbox"/>
TT (Tri Tap 120, 277, 347)	<input type="checkbox"/>

NOTE: Please circle connected voltage. If none is indicated, factory will pre-wire at 120V.

LIGHT SOURCE	
50 - 100 MH	___ W <input type="checkbox"/>
35 - 100 HPS	___ W <input type="checkbox"/>
28PLC Fluorescent	___ W <input type="checkbox"/>
INC Incandescent	___ W <input type="checkbox"/>

OPTICAL SYSTEMS	
BR glass refractor IES type III	<input type="checkbox"/>
BR glass refractor IES type V	<input type="checkbox"/>
LV louver reflector IES type V	<input type="checkbox"/>
OC dual optical cone IES type V	<input type="checkbox"/>
BL bare lamp (recommended for white diffusers only)	<input type="checkbox"/>

OPTIONS	
EB1 single 1" ID steel eye bolt	<input type="checkbox"/>
EB2 double 1" ID steel eye bolt	<input type="checkbox"/>



(800) 267-3175 (905) 238-2648
 1280 Fewster Drive Mississauga
 Ontario L4W 1A4 Canada
 Fax (905) 238-9060
 Email sales@hcilighting.com
 WEB www.hcilighting.com

Lighted Bollard Ordering Sequence Example

BOLLARD — TOP — DIFFUSER — LIGHT SOURCE — VOLT. — OPTICS — OPTIONS — COLOR
B811 — L1 — CPC — 50MH — 120V — BR-5 — EB2 — RAL 9011

Non-lighted Bollard Ordering Sequence

BOLLARD — TOP — OPTIONS — COLOR
B611 — B — EB2 — RAL 9011

B611 SERIES NON-LIGHTED BOLLARD

SPECIFICATIONS

DESCRIPTION: The bollard shall be HCI's _____ (indicate model number, see *Ordering Sequence Example* above). The bollard shall be made from aluminum body with a welded aluminum base plate. A two-piece cast aluminum base cover shall be secured with stainless steel hardware. The lighted bollard shall be equipped with a fixture head on top with a choice of light sources and optical systems. The head shall be secured with four s/s head socket screws. The non-lighted bollard shall be equipped with a decorative cast top, which shall be permanently welded to the bollard.

MATERIALS: The bollard body shall be made from extruded 6"OD aluminum. The base covers shall be made of cast aluminum with a minimum wall thickness of 0.200".

INSTALLATION: The bollard shall be provided with four 3/4"OD x 17"L L-type anchor bolts with two nuts and two washers per bolt, which shall install on an 8-1/2" bolt circle. A sturdy steel template is included.

FINISH: All applicable parts shall receive a standard electrostatically applied thermoset polyester powder coat smooth semi gloss finish with a four part corrosion inhibiting process.

COLORS: The five standard RAL colors are Black 9011, Green 6005, Bronze 8019, Grey 7012 and White 9016. Other colors extra.

OPTIONAL TOPS


A
Pineapple



Q
Half ball



B
Ball



ANCHORAGE DETAILS

