

B815 SERIES LIGHTED BOLLARD

OPTIONAL LIGHTED TOPS

L5 L1 L4

DIFFUSER TYPE

CAC Clear Acrylic

CPC Clear Polycarbonate

WAC White Acrylic

WPC White Polycarbonate

VOLTAGE

QT (Quad Tap 120, 208, 240, 277)

TT (Tri Tap 120, 277, 347)

NOTE: Please circle connected voltage. If none is indicated, factory will pre-wire at 120V.

120V Reactor

480 Single (HPS only, in most wattages)

LIGHT SOURCE

50 - 100 MH _____W

35 - 100 HPS _____W

28PLC Fluorescent _____W

INC Incandescent _____W



(800) 267-3175 (905) 238-2648
 1280 Fewster Drive Mississauga
 Ontario L4W 1A4 Canada
 Fax (905) 238-9060
 Email sales@hclighting.com
 WEB www.hclighting.com

OPTICAL SYSTEMS

- BR glass refractor IES type III
- BR glass refractor IES type V
- LV louver reflector IES type V
- OC dual optical cone IES type V
- BL bare lamp (recommended for white diffusers only)

OPTIONS

- EB1 single 1" ID steel eye bolt
- EB2 double 1" ID steel eye bolt

Lighted Bollard Ordering Sequence Example

BOLLARD — TOP — DIFFUSER — LIGHT SOURCE — VOLT. — OPTICS — OPTIONS — COLOR
B815— L5 — WAC — 50MH — 120V — BL — EB2 — RAL 9011

Non-lighted Bollard Ordering Sequence

BOLLARD — TOP — OPTIONS — COLOR
B615— B — EB2 — RAL 9011

B615 SERIES NON-LIGHTED BOLLARD

SPECIFICATIONS

DESCRIPTION: The bollard shall be HCI's _____ (indicate model number, see *Ordering Sequence Example* above). The bollard shall be made from aluminum body welded to a one-piece cast aluminum base cover. An access door shall be secured with stainless steel hardware. The lighted bollard shall be equipped with a fixture head on top with a choice of light sources and optical systems. The head shall be secured with four s/s head socket screws. The non-lighted bollard shall be equipped with a decorative cast top, which shall be permanently welded to the bollard.

MATERIALS: The bollard shall be made from extruded 5"OD fluted aluminum. The base shall be made of cast aluminum. The castings shall be of uniform wall thickness with a minimum wall thickness of 0.200".

INSTALLATION: The bollard shall be provided with four 3/4"OD x 17"L L-type anchor bolts with two nuts and two washers per bolt, which shall install on an 8-1/2" bolt circle. A sturdy steel template is included.

FINISH: All applicable parts shall receive a standard electrostatically applied thermoset polyester powder coat smooth semi gloss finish with a four part corrosion inhibiting process.

COLORS: The five standard RAL colors are Black 9011, Green 6005, Bronze 8019, Grey 7012 and White 9016. Other colors extra.

OPTIONAL TOPS

A Pineapple

Q Half ball

B Ball

ANCHORAGE DETAILS