

B900 SERIES LIGHTED BOLLARD

OPTIONAL LIGHTED TOPS

L2

L3

DIFFUSER TYPE		VOLTAGE	
CAC Clear Acrylic	<input type="checkbox"/>	QT	<input type="checkbox"/>
CPC Clear Polycarbonate	<input type="checkbox"/>	(Quad Tap 120, 208, 240, 277)	<input type="checkbox"/>
WAC White Acrylic	<input type="checkbox"/>	TT (Tri Tap 120, 277, 347)	<input type="checkbox"/>
WPC White Polycarbonate	<input type="checkbox"/>	NOTE: Please circle connected voltage. If none is indicated, factory will pre-wire at 120V.	
LIGHT SOURCE		120V Reactor	<input type="checkbox"/>
50 - 100 MH	___ W <input type="checkbox"/>	480 Single	<input type="checkbox"/>
35 - 100 HPS	___ W <input type="checkbox"/>	(HPS only, in most wattages)	<input type="checkbox"/>
28PLC Fluorescent	___ W <input type="checkbox"/>		
INC Incandescent	___ W <input type="checkbox"/>		



(800) 267-3175 (905) 238-2648
 1280 Fewster Drive Mississauga
 Ontario L4W 1A4 Canada
 Fax (905) 238-9060
 Email sales@hclighting.com
 WEB www.hclighting.com

OPTICAL SYSTEMS

- BR** glass refractor IES type III
- BR** glass refractor IES type V
- LV** louver reflector IES type V
- OC** dual optical cone IES type V
- BL** bare lamp (recommended for white diffusers only)

OPTIONS

- EB1** single 1" ID steel eye bolt
- EB2** double 1" ID steel eye bolt

Lighted Bollard Ordering Sequence Example

Non-lighted Bollard Ordering Sequence

BOLLARD — TOP — DIFFUSER — LIGHT SOURCE — VOLT. — OPTICS — OPTIONS — COLOR	BOLLARD — TOP — OPTIONS — COLOR
B900 — L6 — CPC — 50MH — 120V — LV — EB2 — RAL 9011	B600 — B — EB1 — RAL 9011

B600 SERIES NON-LIGHTED BOLLARD

SPECIFICATIONS

DESCRIPTION: The bollard shall be HCI's _____ (indicate model number, see *Ordering Sequence Example* above). The body of the bollard shall be made from cast iron. The lighted bollard shall be equipped with an aluminum fixture head on top with a choice of light sources and optical systems. The non-lighted bollard shall be equipped with a decorative cast top. The lighted head or the non-lighted top shall be secured with four s/s head socket screws.

MATERIALS: The body of the bollard shall be made from a spheroidal ASTM A536-65-45-10 Cast Iron casting. The lighted head or the non-lighted top shall be made of cast aluminum. The castings shall be of uniform wall thickness with no warping or mold shifting.

INSTALLATION: The bollard shall be provided with four 3/4"OD x 17"L L-type anchor bolts with two nuts and two washers per bolt installed on a 7-1/2" bolt circle. A sturdy steel template is included. An access door shall be provided in the base of the bollard for ease of installation.

FINISH: The body of the bollard shall be prime painted only. Final finish to be applied in the field. The lighted head or the non-lighted top shall receive a standard electrostatically applied thermoset polyester powder coat smooth semi gloss finish with a four part corrosion inhibiting process.

COLORS: The five standard RAL colors are Black 9011, Green 6005, Bronze 8019, Grey 7012 and White 9016. Other colors extra.

OPTIONAL TOPS

A
Pineapple

Q
Half ball

B
Ball

ANCHORAGE DETAILS